


Spot ONE

Sensor Connect

EAN 4007841 058630



LED

20.000 h

3000K
warm-white

38°

Infrared sensor
90°

max. 10 m



IP44

180° horizontal,
90° vertical2 - 2000 lux (via
App)5 sec - 60 min (via
App)

manual override

Function description

Intelligent and convenient. Modern swivelling LED wall spot ONE Sensor Connect with 90° infrared motion detector (10 m reach). Interconnectable via Bluetooth in next to no time and adjustable via the free app: light-level threshold (2-2000 lux), time setting (5 s – 60 min), ON and OFF times, convenient light grouping. 520 lm from 7 W. Includes replaceable GU-10 LED lamp.

Technical specifications

Dimensions (L x W x H)	175 x 97 x 98 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	2,50 m
Sensor Technology	passive infrared
Output	7 W
Interconnection	Yes
Slave mode/selectable	Yes
Luminous flux	520 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index CRI	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Sneak-by guard	No
Reach, radial	r = 2 m (3 m ²)

Reach, tangential	r = 10 m (79 m ²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No
Functions	Digital timer, Master/slave override
Soft light start	No
Continuous light	selectable, 4h
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	0,477 kg
Version	Sensor Connect
PU1, EAN	4007841058630

Sensor-switched LED floodlight


Spot ONE

Sensor Connect

EAN 4007841 058630



Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m

Orange: radial

Schwarz: tangential

Dimension Drawing

